

US-TSCA-PBT Regulation

Products listed below that are manufactured by Coto Technology are in compliance to the U.S. Environmental Protection Agency (EPA) issued final rules under Section 6(h) On January 6, 2021;the Toxic Substances Control Act (TSCA) for five persistent, bio accumulative and toxic (PBT) chemicals:

- 2,4,6-tris(tert-butyl)phenol (2,4,6-TTBP) CASRN:732-26-3
- Decabromodiphenyl ether (decaBDE)CASRN:1163-19-5
- Hexachlorobutadiene (HCBd) CASRN:87-68-3
- Pentachlorothiophenol (PCTP)CASRN:133-49-3
- PIP (3: 1) Tris phosphate (isopropylphenyl) 68937-41-7

This document certifies that components/s of Part Number as stated below manufactured by Coto Technology do not intentionally added or contain any of the bio accumulative and toxic (PBT) chemicals reported under the TSCA Inventory Notification (Active-Inactive) rule listed above.



Enrique Vasquez
Quality Director

COTOMOS®

Product Series	Package Type	Item weight (grams)	Termination Lead finish	Maximum Process Temp/Time	Compliance date code	MSL
CT1XX	6-pin DIP	0.475	Sn100	250C / 30Sec. Reflow	R353	3
CT3XX	8-pin DIP	0.510	Sn100	250C / 30Sec. Reflow	R353	3
CT4XX	6-pin DIP	0.475	Sn100	250C / 30Sec. Reflow	R353	3
CT6XX	8-pin DIP	0.510	Sn100	250C / 30Sec. Reflow	R353	3
CT7XX	8-pin DIP	0.510	Sn100	250C / 30Sec. Reflow	R353	3
CS1XX	6-pin SMD	0.455	Sn100	250C / 30Sec. Reflow	R353	3
CS3XX	8-pin SMD	0.490	Sn100	250C / 30Sec. Reflow	R353	3
CS4XX	6-pin SMD	0.455	Sn100	250C / 30Sec. Reflow	R353	3
CS6XX	8-pin SMD	0.490	Sn100	250C / 30Sec. Reflow	R353	3
CS7XX	8-pin SMD	0.490	Sn100	250C / 30Sec. Reflow	R353	3
C2XXS	4-pin SOP	0.085	Sn100	250C / 30Sec. Reflow	R353	3
C3XXS	8-pin SOP	0.180	Sn100	250C / 30Sec. Reflow	R353	3
C5XXS	4-pin SOP	0.085	Sn100	250C / 30Sec. Reflow	R353	3
C6XXS	8-pin SOP	0.180	Sn100	250C / 30Sec. Reflow	R353	3
C7XXS	8-pin SOP	0.180	Sn100	250C / 30Sec. Reflow	R353	3
S117T	6-pin DIP	0.295	Cu Ag	260C/10 Sec max Reflow	R19	3
S117S	6-pin SMD	0.295	Cu Ag	260C/10 Sec max Reflow	R19	3

TMR PRODUCTS

Product Series	Package Type	Item weight (mg)	Termination Lead finish	Maximum Process Temp/Time	Compliance date code	MSL
RR1XX	LGA	3.89	N/A	260C	1601	3

REED RELAYS

Product Series	Package Type	Item weight (grams)	Termination Lead finish	Maximum Process Temp/Time	Compliance date code	MSL
1200	Potted THT	6.17	Sn100	270C / 10 Sec. Wave	0525	1
1300	Potted THT	26.47	Sn100	270C / 10 Sec. Wave	0525	1
22XX	Potted THT	1.48	Sn100	270C / 10 Sec. Wave	0525	1
2400-0058	Potted THT	3.62	Sn 100	270C / 10 Sec. Wave	0908	1
23XX	Potted THT	2.48	Sn100	270C / 10 Sec. Wave	0525	1
2362	Potted THT	2.48	Sn100	270C / 10 Sec. Wave	0525	1
26XX	Potted THT	2.60	Sn100	270C/ 10 Sec. Wave	0525	1
29XX	Potted THT	1.94	Sn100	270C / 10 Sec. Wave	0525	1
35XX	Potted THT	10.07	Sn100	270C / 10 Sec. Wave	0525	1
36XX	Potted THT	13.18	Sn100	270C / 10 Sec. Wave	0525	1
4XXX	Potted THT	3.06	Sn100	270C / 10 Sec. Wave	0525	1
50XX	Potted THT	3.06	Sn100	270C / 10 Sec. Wave	0525	1
55XX	Potted THT	39.40	Sn100	270C / 10 Sec. Wave	0525	1
58XX	Potted THT	18.59	Sn100	270C / 10 Sec. Wave	0525	1
7XXX	Potted THT	8.39	Sn100	270C / 10 Sec. Wave	0525	1
82XX	Potted THT	5.04	Sn100	270C / 10 Sec. Wave	0525	1
83XX	Potted THT	4.36	Sn100	270C / 10 Sec. Wave	0525	1
86XX	Potted THT	6.86	Sn100	270C / 10 Sec. Wave	0525	1
87XX	Potted THT	73.56	Sn100	270C / 10 Sec. Wave	0525	1
8000/8L	Molded THT	2.22	Sn100	270C / 10 Sec. Wave	0540	1
9000	Molded THT	1.56	Sn100	270C / 10 Sec. Wave	0545	1
9007	Molded THT	1.56	Sn100	270C / 10 Sec. Wave	0545	1
9011	Molded THT	0.64	Sn100	270C / 10 Sec. Wave	0501	1
9012	Molded THT	0.82	Sn100	270C / 10 Sec. Wave	0501	1
9090	Molded THT	0.92	Sn100	270C / 10 Sec. Wave	0501	1
9091	Molded THT	0.92	Sn100	270C / 10 Sec. Wave	0501	1
9092	Molded THT	1.24	Sn100	270C / 10 Sec. Wave	0501	1
9094	Molded THT	0.95	Sn100	270C / 10 Sec. Wave	0501	1
9081	Molded THT	2.20	Sn100	270C / 10 Sec. Wave	0501	1
9104	Molded THT	3.08	Sn100	270C / 10 Sec. Wave	0501	1
9105	Molded THT	4.2	Gold flash	260C / 60 Sec. Reflow	2543	2
9117	Molded THT	0.60	Sn100	270C / 10 Sec. Wave	0501	1
9200	Molded SMT	0.20	Gold flash	260C / 60 Sec. Reflow	0812	2

TEL: 401-943-COTO ♦ FAX: (401) 942-0920 ♦ www.cotorelay.com
(2686)

929X	Molded SMT	0.20	Gold flash	260C / 60 Sec. Reflow	0816	2
9105	Molded SMT	4.2	Gold flash	260C / 60 Sec. Reflow	2543	2
93XX	Molded SMT	0.20	Gold flash	260C / 60 Sec. Reflow	0641	2
94XX	Molded SMT	0.20	Gold flash	260C / 60 Sec. Reflow	0805	2
9852	Molded SMT	0.20	Gold flash	260C / 60 Sec. Reflow	0825	2
9802/9814	Molded SMT	0.20	Gold flash	260C / 60 Sec. Reflow	0748	2
99XX	Molded SMT	0.20	Gold flash	260C / 60 Sec. Reflow	0601	2
B41	Molded BGA	0.20	N/A	260C / 60 Sec. Reflow	1204	5A

MOLDED SWITCHES

Product Series	Package Type	Item weight (grams)	Termination Lead finish	Maximum Process Temp/Time	Compliance date code	MSL
CT05	Molded SMT	0.12	Sn100	260C / 60 Sec. Reflow	0501	1
CT04	Molded SMT	0.12	Sn100	260C / 60 Sec. Reflow	2522	1
CT10	Molded SMT	0.14	Sn100	260C / 60 Sec. Reflow	0501	1
CM10	Molded SMT	0.12	Sn100	260C / 60 Sec. Reflow	0501	2

TEL: 401-943-COTO ♦ FAX: (401) 942-0920 ♦ www.cotorelay.com
(2686)